



| | | |
|---------------------------------|--------------------------------------|---------|
| Product | Fire rated sectional door (OHD-C) | |
| Product reference | EI(1) 60 / EI(2) 90 / EW 90) | |
| Position number | komposit | |
| Motor side | 30 | |
| | Right | |
| Ax | Clear width | 3500 mm |
| By | Clear height | 3500 mm |
| Cy | Available headspace | 1000 mm |
| Dy | Bottom of consoles | 3945 mm |
| Ey | Height flame hook | 181 mm |
| Ly | Bottom of rail | 4154 mm |
| Lz | Depth of rail | 4449 mm |
| Mx | Required space motorside | 938 mm |
| My | Height motor bracket | 335 mm |
| Ox | Width motor bracket | 156 mm |
| Nx | Distance opening to motor bracket | 355 mm |
| Dz | Distance ceiling brackets | 1232 mm |
| | No. ceiling brackets | 4 sets |
| Connection value | 400 Volt / 2,7 Ampère / 300-900 Watt | |
| Closing speed | Max. ±60 mm/sec | |
| Application temperature | -5 t/m 40 °C | |
| Maximum usage frequency per day | 25 | |
| Number of pallets | 1 | |
| Package 1 | 4648x600x1158 mm | |
| Pallet 1 net weight | 726 kg | |
| Pallet 1 gross weight | 751 kg | |
| Weight door leaf | 484 kg | |
| Model version | 34508 | |

Tolerances for total dimensions

| | |
|---|-----|
| — | 1mm |
| □ | 2mm |
| △ | 2mm |
| ⊥ | 1mm |

Tolerances for supporting construction:
- Required mounting dimensions only +/-
- Clear opening dimensions only -/-

PrinTek-OHDC-NS-1-RIGHT-B