



FIREPRO
HHPK
3P+N+PE
400Volt
16Amp
CEE FORM

±2500

115

60 Ax Sx Mx

See legend on quotation/conformation

Tolerances for supporting construction:
- Required mounting dimensions only +/-
- Clear opening dimensions only -/-

Tolerances for total dimensions
— 1mm
□ 2mm
△ 2mm
⊥ 1mm
RGS_EI-L-Boven

Product	Fire rated roller shutter (RGS EI) - EI(1) 30 / EI(2) 60	
Product reference	Acél	
Position number	10	
Motor side	Left	
Ax	Clear width	3500 mm
By	Clear height	3500 mm
Cy	Built-in height (excl. engine)	1332.52 mm
Dy	Bottom of consoles / Top-level guides	3925.52 mm
Ex	Space motor side	374 mm
Fx	Space non-motor side	299 mm
Gy	Height flame hook	3800 mm
Hx	Console width	80 mm
Mx	Guide width	150 mm
Kx	Total width	4173 mm
Ly	Total height (excl. engine)	4832.52 mm
Nx	Distance between consoles	3920 mm
Lz	Console depth	876 mm
Ky	Motor height	472 mm
Sx	Distance between guides	3620 mm
Connection value	400Volt / 1,5 Ampère / 300 Watt	
Closing speed	60-100 mm/sec	
Application temperature	-5 t/m 40 °C	
Maximum usage frequency per day	25	
Weight door leaf	517	
Number of pallets	3	
Package 1	4072x900x950 mm	
Pallet 1 net weight	647	
Pallet 1 gross weight	672	
Package 2	3875x600x500 mm	
Pallet 2 net weight	194	
Pallet 2 gross weight	219	
Package 3	1200x800x900 mm	
Pallet 3 net weight	240	
Pallet 3 gross weight	265	
Model version	11577	