



FIREPRO
HHPK
3P+N+E
400Volt
16Amp
CEE FORM

±2500

Tolerances for total dimensions

—	1mm
□	2mm
△	2mm
⊥	1mm

Tolerances for supporting construction:
- Required mounting dimensions only +/+
- Clear opening dimensions only -/-

RGS_EI-L-Boven

See legend on quotation/conformation

Product	Fire rated roller shutter (RGS EI) - EI(1) 30 / EI(2) 60
Product reference	Acél
Position number	10
Motor side	Left

Ax	Clear width	3500 mm
By	Clear height	3500 mm
Cy	Built-in height (excl. engine)	1332.52 mm
Dy	Bottom of consoles / Top-level guides	3925.52 mm
Ex	Space motor side	374 mm
Fx	Space non-motor side	299 mm
Gy	Height flame hook	3800 mm
Hx	Console width	80 mm
Mx	Guide width	150 mm
Kx	Total width	4173 mm
Ly	Total height (excl. engine)	4832.52 mm
Nx	Distance between consoles	3920 mm
Lz	Console depth	876 mm
Ky	Motor height	472 mm
Sx	Distance between guides	3620 mm

Connection value	400Volt / 1,5 Ampère / 300 Watt
Closing speed	60-100 mm/sec
Application temperature	-5 t/m 40 °C
Maximum usage frequency per day	25

Weight door leaf	517
Number of pallets	3
Package 1	4072x900x950 mm
Pallet 1 net weight	647
Pallet 1 gross weight	672
Package 2	3875x600x500 mm
Pallet 2 net weight	194
Pallet 2 gross weight	219
Package 3	1200x800x900 mm
Pallet 3 net weight	240
Pallet 3 gross weight	265

Model version	11577
---------------	-------